

7450-XLP



RF Subscriber Unit for Alarm Transmission with Full Data Transfer



- 4 Programmable Zones
- Integrated IntelliPro
- Supports Contact ID, Pulse, Modem formats
- Telephone line cut monitoring with 1, 2, 3 minute delay

Available Configurations

- 7450-XLP Standard Case With IntelliPro
- 7450-XLT Standard Case

Advanced Wireless Alarm Monitoring

The 7450-XLP smart subscriber unit links an alarm panel to an alarm monitoring central station. This 2-way transceiver and repeater in one is housed in a full size locking steel cabinet for superior performance. The 7450-XLP supports a wide range of inputs such as NO /NC/EOL and direct voltage. It automatically senses phone line cuts and antenna cuts, and monitors battery and AC power status. The built in power supply with advanced status reporting and self-diagnostics make the 7450-XLP the first choice for all wireless monitoring needs.

Integrated IntelliPro Provides Full Data

The integrated IntelliPro monitors the alarm panels' digital communicator output. In normal operation the alarm panel dials the IntelliPro designated phone number as the primary central station receiver. The IntelliPro detects this information and receives the data just like a dialer receiver providing handshake protocols to authenticate a successful transfer. The alarm data is then forwarded via the AES-IntelliNet RF wireless network to the central station. The 7450-XLP is available without the integrated IntelliPro. Please specify the 7450-XLT.



Wireless mesh networking is an innovative technology adopted by many industries with applications that need to communicate data over a large geographic area with a high level of reliability at a low total cost of ownership.

The advanced design and 2-way communications capability provides easy installation, expansion, and management when compared to alternative communication methods, both wired and wireless.

7450-XLP

Technical Specifications

7450-XLP Subscriber Unit

Radio

Standard CSAA frequency ranges:

- UHF - 410-470 MHz (and others)
- VHF - 150-174 MHz (and others)

Standard Output Power

- 2 watts (requires FCC license, or equivalent)
- Optional 5 Watts (International only)

Power Input

16.5 VAC, 30VA

Voltage

12 VDC nominal

Current

175mA standby; 800mA transmit

Alarm Signal Inputs

- 4 individually programmable Zones: NO/NC/EOL, trouble restore
- Telephone line cut monitor
- Integrated IntelliPro Dialer Capture Module (with XLP configuration)
- RS-232

Operating Temperature Range

0° to 50° C

Storage Temperature Range

-10° to 60° C

Relative Humidity Range

0-85% RHC non-condensing

Back-up Battery

12V, 4.5 AH option

Low Battery Reporting

- 22.5-minute test cycle

AC Status

- Reports to central station after approximately 4 minutes without AC power
- Reports power restoration after approximately 4 minutes of restored power
- Antenna cut (local reporting)
- Open collector output, 200mA maximum load

Size

13.25"H x 8.5"W x 4.3"D

34 cm x 21.5 cm x 11 cm

Weight

XLP 6.8 lbs / 3.1 Kilograms (excluding battery)

XL 6.5 lbs / 2.9 Kilograms (excluding battery)

IntelliPro Module

(Only with XLP Configuration)

I/O Connections

- RS232 data link
- Incoming phone line
- Phone output from alarm panel
- House phone

*Formats Supported

- 3+1, 4+1, 4+2
- Contact ID/Point ID, Modem formats

Controls

- 1 reset switch
- Jumper pins for programming

Central Station Requirements

- AES receivers V1.65 or higher
- AES NET7K V1.49 or higher

*For additional formats supported updates visit:
www.aes-intellinet.com/AES-IntelliNet_7094IntelliPro.html



For more information

Call 800-AES-NETS (800-237-6387)

AES-Intellinet | 285 Newbury Street | Peabody, MA 01960

Tel. 1-978-535-7310 | Fax 1-978-535-7313 | Email info@aes-intellinet.com

Web www.aes-intellinet.com

AES-IntelliNet is the industry leader in delivering high quality wireless mesh networks to the fire and security industry in commercial, corporate, government, and educational applications with its broad line of products and advanced network management tools. Users of AES-IntelliNet networks have gained significant revenue, communications, and cost advantages while meeting the high standards of reliability required for the fire and security industry. AES-IntelliNet alarm monitoring systems are deployed at hundreds of thousands of locations in over 50 countries.

Copyright 2011 AES Corporation
AES-Intellinet is a registered trademark of AES Corporation

7450xlp/11/01/R3